

# CLEANCOLL SP

## Purpose paint remover

---

- ▷ **Removes paints, varnishes, coatings**
  - ▷ **Gel, ideal for use on vertical surfaces**
  - ▷ **Deep penetrating action**
  - ▷ **Removes up to 10 layers in one application**
- 

### Description

CLEANCOLL SP is a powerful, all-purpose paint remover. It's a gel and makes it ideal for both vertical and horizontal surfaces. It is applied on mineral and building surfaces, metals, wood without corrosion. Its deep penetrating capacity makes it ideal for quick and easy removal of all types of paints, varnishes, plastic coatings, epoxy and polyurethane coatings. Usually only one application removes more than one layer of color. It contains no phenols and chlorinated hydrocarbons.

---

### Uses

CLEANCOLL SP can be applied to facilitate stain removal in the following cases:

- Remove any type of paint, graffiti, etc.
  - Enamel varnish and plastic coatings
  - Residues of contact adhesive
  - Epoxy and polyurethane dyes
  - Lacquers, shellac, tar and many other coatings
  - Residues of glue and epoxy grouts created during welding and grouting of ceramic tiles
- 

## Technical Data

### Product Identity

---

Form	Gel
Color	Yellowish
Chemical Base	Mixture of solvents
Density	0,98 ± 0,05 kg/L

---

## Application procedure

**Application** Before applying CLEANCOLL SP, protect any surface that may be damaged when in contact with solvents. Apply CLEANCOLL SP as it is without thinning uniformly to a thick layer with a brush partially on surfaces of up to 0.5 m<sup>2</sup> at a time. When the coating has been softened (5 - 10 minutes) with a soft brush or cloth lightly rubbing the surface, remove the residue. At difficult points, repeat the process if necessary. Finally rinse the surface with cold water and detergent.

**Recommendations** Do not apply:

- Rubber, polystyrene, vinyl flooring, etc.
- It is not compatible with synthetic fabrics and fiberglass
- Do not use it in good quality wood without testing
- Avoid using in cases where the substrate and environment temperature is less than +5°C or higher than +35°C
- Use only in a well-ventilated area
- Do not use it with hot air guns or near an open flame or other ignition source
- Keep out of reach of children

**Consumption** Depending on the application 200 – 300 gr/m<sup>2</sup>.

**Storage** CLEANCOLL SP remains stable for at least 12 months from production date, in its sealed original packing, stored in dry conditions and temperatures between +5°C and +30°C.

**Packaging** Containers of 1Kg

**Safety Instructions** For further information refer to the Safety Data Sheet of the product.

## Warning

The technical data and recommendations contained in this leaflet correspond to the best of our knowledge and experience. All the above mentioned information in any case should be considered as merely indicate and subject to confirmation after long term practical applications. In practice, variations in materials, substrates and on-site implementation conditions are such that no warranty can be given on their merchantability or suitability for a particular purpose, and no liability whatsoever from any legal relationship can be claimed against the Company on the basis of any written information, written suggestions tips or other forms of instructions provided. For this reason anyone interested of using the product must be sure beforehand that the product is suitable for the envisaged application. In every case the user alone is fully responsible for any consequences deriving from the use of the product. We retain the right of renewal of the data of the leaflet without warning. For the latest and valid version of the Technical Data Sheet refer to use website [www.novamix.gr](http://www.novamix.gr) or directly to the following QR code of the product.



DOMOCHNEMICAL SA  
40 PAPANIKOLI STR  
CHALANDRI 15232  
ATHENS GREECE  
T +30 210 68 93 953  
F +30 210 68 94 571  
[novamix@novamix.gr](mailto:novamix@novamix.gr)